BTE ATTACHMENT

MULCHER

Clear land and control brush in challenging terrains.

The **BTE Mulcher** powers high-production mulching for right of ways and medians, quickly eliminating dense vegetation to improve visibility and ramp up productivity. With durable tungsten carbide cutting teeth, the excavator-mounted system grinds trees up to six inches in diameter and minces dense brush while operators stay in a safe position, on or off-track.

AT-A-GLANCE

Height/Length	46” x 64” (1,169 mm x 1,626 mm)
Width	64” (1,626 mm)
Weight	2,400 lbs (1,089 kg)
Auxiliary Hydraulic Circuits Required	2
Door Cylinder Reqs.	10 Max GPM/3,000 Max PSI (37 l/m/20,864 kPa)
Drive Motor Reqs.	40 Max GPM/3,500 Max PSI (151 l/m/20,864 kPa)
Hydraulic Case Drain Circuit Reqs.	1
Hydraulic Flow Reqs.	26 to 53 GPM (98 to 200 l/m)
Hydraulic Pressure Reqs.	2,600 to 3,600 PSI (17,926 to 2,481 kPa)

FEATURES

- 360 degree rotation with Rototilt
- Horizontal 53-inch cutting width
- 36 fixed tungsten carbide cutting teeth
- Tungsten carbide teeth provide maximum durability
- Grinds trees up to six inches in diameter
- Safety guards control flying debris

BALLAST TOOLS™ BTE EQUIPMENT